

Tilt buckets XHD



Tough buckets for hard use

Special wear steel for high durability

Central lubrication nipple for main bolt, connection with central greasing (option) is possible

Completely covered hydraulic cylinders*

Shock valve prevents damages in the hydraulic system due to overstress

Oil line adjacent on main bolt, very short hoses


WIMMER EOP-Covers: Easy to open even when dirty or damaged **




^{*} E15, E30 und E33: Hydraulic cylinders only partially covered ** not available for Tiltor 04 and 05




Various XHD tilt buckets




Tiltor 4A, Model E15 Excavator: 3 bis 6 to



Tiltor 5A, Model B20 Excavator: 6 - 10 to




Tiltor 6A, Model B20 Excavator: 8 - 12 to




Tiltor 6A, Model B31 (round B32) Excavator: 12 - 14 to


Tiltor 7A, Model E30 / E33 Excavator: 14-18 to / 18-22 to



Tiltor 7A, Model B33 (also rounded version)



Tiltor 7A, Model B34 / B35 / B36 16-20 to / 18-22 to / 20-22 to



Tiltor 8A Model B36 / B40 / B43 Excavator: 20-24 / 22-28 / 24-30 to




Tiltor 8A, Model L30 Excavator: 24-32 to





Tiltor 9A, Model L25, L30, L33, L35, L40, L43




Tiltor V8, Model L30 / L33 / L35 / L43 Excavator: 24-32 / 32-38 / 32-47 / 38-47 to






Advantages of the Tiltor models











WIMMER Hartstahl GmbH & Co KG and WIMMER Felstechnik GmbH Industriestraße 3, A-5303 Thalgau, AUSTRIA, Tel. +43 (0)6235 6655-0, Fax DW-18

WIMMER International CZ s.r.o., Rudolfovská 170 a, 370 01 České Budějovice, Tel. +420 387 203 735, Fax +420 387 203 736

office@wimmer.info



Authorized WIMMER Dealer:

rights and technical changes reserved. Copyrighted. Record and printing errors reserved.