

Drilling Unit AB 2600 T | AB 2600 T Climb



Drilling data evaluation with the Wimmer Cockpit



Options for all systems

- Clamp breaking device
- Angle indication
- Dust collector
- Compressor on the excavator
- PLC automatic
- Wimmer Cockpit
- Reinforced feed
- Rod changer
(not with Climb-Version)

Standard equipment

- ✓ Hose roller
- ✓ 360° endlessly rotatable, 90° tiltable
- ✓ independant electric power supply
- ✓ Radio remote control - all drilling functions proportionally controlled
- ✓ Blank firing protection
- ✓ Anti-jamming automation
- ✓ Hollow protection

Drilling Unit AB 2600 T | AB 2600 T Climb



Range of application

- Injection anchor drillings
- Anchor and blast hole drillings
- Down-the-hole drilling / Overburden drillings
- Double-head drillings

Strong drilling unit for excavators >20 tons

- Attachment to crawler excavators and walking excavators
- Large selection of carriage - hammer - combination
- Light and stable high performance profile
- Large standard equipment package, many additional options



	AB2600 T50	AB2600 T-50D	AB2600T-5 Double Head	AB2600 T-510
Drill Hammer	RH 4 X - 20	RH 4X	DH 4	WHL 510
Weight (kg)	ca. 1750 1870	ca. 1800 1920	ca. 1800 1920	ca. 1750 1870
Standard Climb				
Drilling diameter max. (mm)	200 rotary drilling	200 rotary drilling	200 rotary drilling	89
Torque (Nm)	2500 / 5000 switchable	2500 / 5000 switchable	1060 / 2120 inner 2500/5000 outer	625
Drilling Unit- Shenk adapters				
Blasthole drilling	T38, T45, T76	-	-	R32, T38,T45
Anchor drillings	R32, R38, R51, IB30, IB40, IB52	-	-	-
Down-the-hole-drilling/Double Head	mit Spülwelle API 2 3/8"	API 2 3/8"	Double Head until 200 mm	-
Rod length (mm)	3050 3050	3050 3050	3050 3050	3050 3050
Standard Climb				
Total length (mm)	5720 5720	5720 5720	5440 5440	5920 5920
Standard Climb				
Oil supply (L/min)	180 @ 200 bar	125 @ 200 bar	175 @ 200 bar	170 @ 170 bar
Required motor performance (kW)	75	52	73	60
Oil pressure @excavator (bar)	250 > 20	250 > 20	250 > 20	250 > 20
Execution				
Rotation/Tilting	360° not endlessly rotatable/ 90° tiltable	360° not endlessly rotatable/ 90° tiltable	360° not endlessly rotatable/ 90° tiltable	3360° not endlessly rotatable/ 90° tiltable
Feed shift (mm)	550 780	550 780	550 780	550 780
Standard Climb				
Clamping device	single	Clamp-break	Clamp-break	single

Eurodrill RH 4 X



DH4 double head drilling system



Rod Clamping with suction foot



Clamp-Breaking Device



Hose Roller