

## Drilling Unit AB 4600




### Range of application

- Blast hole drillings

### High performance device in the quarry for excavators >25 tons

- for efficient hammer drilling
- Rod changer single/3-/5-fold available
- Light and stable high performance profile
- Large standard equipment package, many additional options



# Technical Details AB 4600

	AB 4600 T-510	AB 4600 T-710
Drill Hammer	WHL 510	WHL 710
Weight (kg)	ca. 2100	ca. 2300
Drilling diameter max. (mm)	89	115
Torque (Nm)	625	1095
<b>Drilling unit - shenk adapters</b>		
Blasthole drilling	R32, T38, T45	R38 / T45 / T51
Rod length (mm)	3660	3660
Total length (mm)	6430	6430
Oil supply (L/min)	170 @ 170 bar	230 @ 200 bar
Required motor performance (kW)	60	96
Oil pressure @excavator (bar)	200	230
Carrier to	> 25	> 25
<b>Execution</b>		
Feed shift (mm)	1180	1180



## Options for all systems

- Clamp breaking device
- Angle indication
- Dust collector
- Compressor on the excavator
- PLC automatic
- Wimmer Cockpit
- Reinforced feed
- Single/3-/5-fold rod changer

## Standard equipment

- ✓ Rod clamping device
- ✓ Hose roller
- ✓ 360° endlessly rotatable, 90° tiltable
- ✓ independant electric power supply
- ✓ Radio remote control - all drilling functions proportionally controlled
- ✓ Blank firing protection
- ✓ Anti-jamming automation
- ✓ Hollow protection

WIMMER Hartstahl GmbH & Co KG und WIMMER Felstechnik GmbH  
 Industriestraße 3, A-5303 Thalgau, AUSTRIA, Tel. +43 (0)6235 6655-0

office@wimmer.info

[www.wimmer.info](http://www.wimmer.info)

